



DAFA Facade Kit™ Butyl 200 joint sealant

Description

Butyl 200 is a non-hardening joint sealant used for sealing in a range of structures.

Application

For sealing purposes on a wide range of structures, where the butyl is applied in a "tight fit joint". This means areas where there is a form of mechanical fixing (e.g. between a concrete floor and a floor sill). Used for instance in overlapping joints in moulding for caravans and for sealing joints in roof structures.

Information

- Colour: Light grey
- Good UV-resistance
- Good resistance against acids and alkalis.
- The surface must be kept clean, dry and free of oil and grease.
- Can be stored for up to one year (in a dry, cool and frost-free environment)



For bonding overlaps and flashing to foundation wall plates.



Butyl 200, tube 310 ml.



Butyl 200, bag 580 ml.

Please contact our customer service department for further information on +45 87 47 66 66

Technical specifications	
Material	Non-hardening butyl joint sealant
Temperature resistance	-40°C to +80°C
Installation temperature	+5°C to +30°C
Storage	One year. Store in a dry, cool and frost-free environment.
Density	1.6 g/cm ³
Resistance	Good UV-resistance. Good resistance against acids and alkalis.
Colour	Light grey

Type/contents	Contents per box	DAFA item no.	EAN no.	TUN no.
Tube, 310 ml	25 tubes	233400100	5705636098944	7974765
Bag, 580 ml	12 bags	620010694	5705636313764	1374824